




PAC C110




ELECTRONIC CONTROL PANEL

PAC C110 is the perfect appliance to always have the desired climate anywhere it is needed. It uses the most advanced technology to maximize its cooling capacity.



REMOTE CONTROL

The remote control allows an easy setting of all the functions and parameters of the unit



TECHNICAL DATA

Dimensions (hwxwd)	mm	773x463x372
Weight	Kg	32
Rated voltage/Frequency	V-Hz	230-50
Cooling capacity	Btu/h-W	11000 - 3220
Input power	W	1050
Energy efficiency class		B
EER		2.51
Annual energy consumption	kWh	525
Air flow	m ³ /h	240-330
Moisture removal	l/24h	24-27
Noise Level	db(A)	51-55
Recommended room size		85m ³
Gas		R410a

PAC C110

- Cooling capacity: 11000 Btu/h.
- Recommended for rooms up to 85 m³.
- Removes up to 24 l/d of excess moisture while conditioning
- Only dehumidification function, removes up to 27 l/d of excess moisture.
- 3 fan speeds.
- 24 hour digital timer and thermostat.
- Electronic controls with microprocessor.
- Autofan and AUTO function: the air conditioner automatically sets the fan speed and the operation mode according to the actual temperature in the room.
- Remote control with LCD.
- Refrigerant gas R410A



Living innovation

AIR-CONDITIONING & AIR-TREATMENT APPLIANCES